



# **Gladiator Equipment**

---

**Inc.**

## **GLADIATOR EQUIPMENT INC. EXTENDABLE PIPETRAILER GENERAL SPECIFICATIONS**

**MODEL: DO-40-4-4-WB-RS**

**MODEL: 40 TON 4 AXLE REAR STEER EXTENDABLE  
PIPETRAILER**

## **GENERAL SPECIFICATIONS**

### **Main Frame:**

Fully fabricated steel frames'

10'-0" platform when closed is capable of transporting 35ton distributor over 30ft.

10'-0" wide sliding chalk blocks are mounted at the front and rear of the deck to allow the dolly to be used in a pipe hauling application.

Fabricated turntables with an UHMW wear pad for reduced friction and wear during steering.

The turn tables are able to lock straight using a manual pin.

Comes with a simple A-frame tow bar at each end with a drop type pin hitch.

The draw bars come with a spring support to allow one man to easily connect and disconnect the dolly from the prime mover.

### **Load securement:**

Chain pockets mounted on 24" centers throughout the deck

Winches mounted on 36" centers along deck

### **Running Gear:**

Suspension: walking beam suspension

Axle spacing: 60" (to be confirmed during engineering)

Axles: (4) 25,000 lb. capacity per axle (nominal)

Tires: (4) 710/45R22.5 flotation tire

Wheels: (4) 20.00x22.5 Steel flotation wheel

Hubs: 10-stud, hub piloted, Unimount

Drums: outboard mount

Spiders: Weld-on

Brakes: Manual parking brake

### **Air:**

No air system is required

### **Electrical:**

No electrical system is required

### **Paint:**

Sandblasted, primed (two-part Ultra Grip primer) and painted single colour (two-part plastic paint) with conspicuity tape to meet US and CDN FMVSS. spicity tape to meet US and Canadian FMVSS